



Yuasa Technisches Datenblatt

Yuasa YBX3077 - YBX3000 SMF Batterien

Leistung

Spannung	12V
Kapazität 20 Std (vorgegeben)	45Ah
Kaltstartstrom (A) EN1	380A

Abmessungen

Länge	207mm
Breite	175mm
Höhe	190mm

Maße und Gewichte

Durchschnittliches Gewicht inkl. Säure	12.7kg
--	--------



Gehäuseeigenschaften

Gehäusotyp	L1 DIN
Zellenanordnung	1
Batteriehälter	B3
Ladezustandsanzeige	✓
Tragegriffe	✓
Entgasung	✓
Deckeltyp	SMF doppelwandige Deckelkonstruktion


Technologie

Flammschutz	✓
Technologie	Ca/Ca
Adskiller	PE
VDA Überschlagentest	✓
Empfohlener Ladestrom	3A
Performance Marking	W3-C2-V2-E1


Anschlusspol Typ

T1

Standard DIN Post




Positive Terminal




Negative Terminal

Zellenanordnung



1

Batteriehälter



Datenblatt erstellt am 13/06/2024 - E&EO



Yuasa Technical Data Sheet

Yuasa YBX3077 - YBX3000 SMF Batteries

Performance

Voltage	12V
Capacity (20-hour)	45Ah
Cold Cranking Amps (EN1)	380A

Dimensions

Length	207mm
Width	175mm
Height	190mm



Weights & Measures

Mean Weight with Acid	12.7kg
-----------------------	--------

Container Features

Case Type	L1 DIN
Cell Layout	1
Hold Down	B3
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid

Technology

Flame Arrestor Technology	✓
Separator	Ca/Ca
VDA Roll Over Test	PE
Recommended Charge Rate	✓
Performance Marking	3A
	W3-C2-V2-E1

Terminal Type

T1


Standard DIN Post




Positive Terminal

Negative Terminal

Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 13/06/2024 - E&OE

